

Modeling Results

Stable RUNOFF and EXTRAN runs were obtained for all modeling scenarios, with EXTRAN continuity errors well below 0.5 percent.

Boundary conditions (water surface elevations) at the downstream outfall were set in accordance with Chapter 5, Section Q of the City of Chesapeake Public Facilities Manual (July 2001 Edition). In all cases, for all return periods, the hydraulic boundary condition was modeled as a constant water surface elevation of 3.55 feet (NAVD88).

The GIS analysis prepared in support of this modeling indicates that the New Mill Creek watershed will increase from **17.2** to **27.9** percent imperviousness in the future, as indicated in Figures 3 and 4. The procedures used to determine this increase are explained in the *Master Drainage Plan Methodology* (April 2005) report submitted previously. This increase in impervious cover produces greater volumes of storm water runoff, which have been incorporated into the future conditions models.

Figures 7 and 9 depict street and property flooding volumes for the 10- and 50-year design storm events. The histograms are not drawn to any scale, but they are proportional, and serve to graphically identify where flooding can be expected under each modeling configuration.

The City does not have to ‘fix’ all of the flooding represented by the histograms in the figures. Areas such as deep ravines, large open spaces, ball fields and parks, and along railroad rights of way often do not require improvements unless there is a specific reason to construct them. It is also important to bear in mind that a 50-year design storm is an extreme event, and that neighborhood drainage systems are typically not required to accommodate 50-year storms.

Flooding complaints, particularly those in residential neighborhoods, often result from maintenance problems such as a clogged pipe or debris in a ditch. In considering whether or not drainage improvements might be required to correct an *existing* deficiency, the model results should indicate a flooding problem, and there should be some flooding history to support the need for improvements. If both of these conditions are not met, then the system maintenance should be reviewed or the computer models should be carefully checked.

It is also important to understand when reviewing these results that there can be low-lying structures in the watershed that have finished floor elevations below the maximum water surface elevations computed in the SWMM models. In order to estimate whether or not a particular structure will be subject to flooding for a given storm condition, maximum hydraulic grade line elevations in the vicinity should be checked against the finished floor elevation.

As with all models of this size and complexity there is a great deal of detailed information required. Because it is not feasible to collect *all* of the required data, in some locations it is necessary to make educated guesses about inverts and pipe and channel dimensions and geometries. Where future designs and studies will be based on these models, engineers are strongly encouraged to field-verify all items that may critically impact their designs.

The peak computed water surface elevations at each model node are presented in Appendix C for both existing and future conditions, and for the environmental restoration scenario. The **blue shading** in Tables C-1 through C-3 indicates locations where the maximum computed water surface meets or exceeds the ground elevation for the node. Many of these nodal flooding

locations are very small quantity or short duration events. In the SWMM EXTRAN models, the volume of water leaving the node during flooding is computed and summarized for continuity purposes (which allows for a reasonable accounting of flood volume at the node) *but the flooded water is not re-introduced into the model for subsequent routing*. If flooding occurs at a choke point in the system, downstream nodes may have computed maximum water surface elevations less than what can actually be expected due to the volume of water being ‘held’ upstream. At nodes in Tables C-1 through C-3 where this phenomenon is probably occurring the maximum computed water surface is indicated in ***bold, red, italic*** type. The patterns of flooding can appear to be somewhat counter-intuitive due to the complexity of hydraulic routing. For example, a given node can flood for the 10-year event, but not for the 25-year event. This could be due to computed upstream flooding, or it could be due to the timing of flooding along other hydraulic pathways.

The figures that indicate nodal flood volumes in this report have been filtered so that nodal flood volumes less than 10,000 cubic feet are not represented (because less than 10,000 cubic feet of flooding cannot be practically discerned on the ground—it simply appears as heavy runoff or sheet flow in most cases). Tables C-1 through C-3 have not been filtered at all; where nodal flooding is indicated in many cases the duration and quantity of flooding can be very minor.

The PCSWMM modeling platform contains a very helpful dynamic hydraulic grade line tool that allows the user to view animations of the computed water surface elevations. This dynamic hydraulic grade line tool takes input from a digital interface file at *a specified sampling interval*, for example every 3 minutes in these models. The EXTRAN routing computations are performed at one-second intervals, and the EXTRAN output (*.out) file contains summary information based on *every* time step. If the dynamic hydraulic grade line tool is used to view the results the user should bear in mind that it is based on a sample (one out of every 180 seconds), and therefore the ‘peak’ values listed by the dynamic hydraulic grade line tool are peaks as sampled using a three-minute interval. The EXTRAN output data on the other hand contains a summary of the *exact* peak values. The EXTRAN output file summaries are used to prepare Tables C-1 through C-3, and as well as the flooding figures in this report.

The modeling results presented in this report are based on the assumption that the drainage and storm water systems will be well maintained. If debris builds up to block drainage structures, or channels are allowed to fill with silt, flooding will likely be more severe than computed and represented in this report.

FEMA flood insurance studies and rate maps are the definitive source of floodplain limits and elevations in all cases. The SWMM models developed for this drainage study are specific design scenarios based on 2-, 5-, 10-, 25-, 50-, and 100-year rainfall events—**THEY ARE NOT TO BE CONSTRUED AS INDICATIVE OF EXPECTED WATER SURFACE ELEVATIONS FOR THE PURPOSES OF FLOODPLAIN MANAGEMENT AND/OR INSURANCE REQUIREMENTS**. The SWMM models developed for this study could be adapted for use in the National Flood Insurance Program and submitted to FEMA for approval, but until they are subjected to that process the published flood insurance studies and rate maps remain fully in effect.