

SHOWER LINER TEST CERTIFICATION - SCHLUTER SYSTEMS

The Virginia Construction Code and referenced International Residential Code requires a shower liner test to be conducted to ensure that the shower floors and receptors are made water tight. The test requires the following:

- 1) The floor and receptor area shall be filled with potable water to a depth of not less than two inches measured at the threshold.
- 2) Where a threshold of at least two inches thick does not exist, a temporary threshold shall be constructed to retain water in the lined floor to a level not less than two inches deep measured at the threshold.
- 3) The water shall be retained for a test period of not less than 15 minutes and there shall be no evidence of leakage.

Persons installing a Schluter Shower System and installing the shower drain assembly after the rough-in plumbing inspection has been performed may, in lieu of a plumbing inspection, provide certification that the above noted shower liner test has been performed in accordance with the IRC and per the product manufacture's specification (whichever is the most restrictive testing method).

I hereby certify the installation and liner test of the Schluter Shower System was performed by persons trained and/or proficient in the installation of such systems in accordance with the aforementioned test as required by the IRC and the product manufacture's specifications:

Permit Number: _____ Job Address: _____

Phone #: _____ E-Mail: _____

Signature of Building Contractor/Owner: _____ Date: _____

Official Use Only

Approved By: _____

Date: _____

*"The City of Chesapeake adheres to the principles of equal employment opportunity.
This policy extends to all programs and services supported by the City."*